

PRODUCT DATA SHEET

EDGE CHEM JAMAICA LIMITED
18 Carifta Avenue
Kingston 11, Jamaica
Tel: (876) 937-3831-4 Fax: 937-3838
E-mail: edge@cwjamaica.com
Website: www.edgechem.com

COLOR GLOW FLAT EMULSION

Rev. 2 T.D.S.

DESCRIPTION

Color Glow Flat Emulsion is a quality styrene acrylic paint designed for long term durability on a variety of interior and exterior surfaces. Its excellent properties and low cost makes it the best value for money paint available.

PERFORMANCE FEATURES

- Interior & exterior durability
- Non-toxic
- Resistant to fungus, mildew and weathering
- Very low odour
- Easy application
- Excellent scrub ability
- High hiding
- Excellent color retention
- Resistant to cracking and peeling

PHYSICAL PROPERTIES

Specific Gravity (g/cm ³)	: 1.3 ± 0.1
Finish	: Flat
Gloss	: ≤ 5°/85°
Viscosity	: ~ 4500 cPs
Flash Point	: Water-based
Drying Time (31° and 70% RH):-	
To Touch	: approximately 15 minutes (Dependent on temperature and relative humidity)
To Re-coat	: after 1 hour


Colours : White, Off-White, Gardenia, Teenage Pink, Morning Glory, Mint Green, Ash Grey, Dusty Grey, Aquamarine, Paw Paw, Whisper, Warm Cream, Raspberry, Sunshine Yellow, Bone White, Olive Green, Surf Blue, Lilac, Black, Blue Blossom, Blue Lagoon, Harvest Yellow, Mango Squash, Hot Sauce

COVERAGE RATE

Approximately 400 ft²/gallon at 1.5 mils DFT dependent on surface porosity.

SUGGESTED USES

On properly primed surfaces including wood, vinyl, aluminum, drywall, wood trim, window masonry, galvanized and ferrous metal.



PRODUCT DATA SHEET

EDGE CHEM JAMAICA LIMITED
18 Carifta Avenue
Kingston 11, Jamaica
Tel: (876) 937-3831-4 Fax: 937-3838
E-mail: edge@cwjamaica.com
Website: www.edgechem.com

COLOR GLOW FLAT EMULSION

Rev. 2 T.D.S.

SURFACE PREPARATION

Surface must be free of dirt, grease, wax, rust, mildew, fungus, chalk and peeling paint. Glossy surface should be sanded. Check adhesion to suspected alkyd or oil paint in an area prior to applying latex coatings. If an adhesion problem is present, prime with a suitable primer to form an intermediate coat. New or unpainted surfaces should be cured properly then coated with one (1) coat of EDGE CHEM CONCRETE SEALER before application.

APPLICATION

Stir Color Glow Flat Emulsion thoroughly before application. If using a brush or roller no reduction is required – use full body. If necessary, thin with water, no more than ½ pint per gallon. If spraying, reduction of up to 1 pint of water per gallon is allowed.

SHELF LIFE

2 years

CLEAN-UP

This should be done immediately using clean water. Wash out brushes, rollers and hands immediately after painting.

