

PRODUCT DATA SHEET

EDGE CHEM JAMAICA LIMITED
18 Carifta Avenue
Kingston 11, Jamaica
Tel: (876) 937-3831-4 Fax: 937-3838
E-mail: edge@cwjamaica.com
Website: www.edgechem.com

COLOR GLOW LOW SHEEN EMULSION

Rev. 2 T.D.S.

DESCRIPTION

Color Glow Low Sheen Emulsion is a premium quality pure acrylic paint designed for long term durability on a variety of interior and exterior surfaces. Its beautiful low sheen finish makes it suitable for those hard use areas such as kitchens, bathrooms and children's rooms as it is easy to wipe clean of dirt, oils and grease.

PERFORMANCE FEATURES

- Interior & exterior durability
- Non-toxic
- Resistant to fungus, mildew and weathering
- Very low odour
- Easy application
- Excellent scrub ability
- High hiding
- Excellent color retention
- Resistant to cracking and peeling
- Resistant to dirt, grease and oils

PHYSICAL PROPERTIES

Specific Gravity (g/cm ³)	: 1.2 ± 0.1
Finish	: Low Sheen
Gloss	: 16-18 °/85°
Viscosity	: 4500-5000 cPs
Flash Point	: Water-based
Drying Time (31° and 70% RH):-	
To Touch	: approximately 15 minutes (Dependent on temperature and relative humidity)
To Re-coat	: after 1 hour


Colours : White, Off-White, Gardenia, Teenage Pink, Morning Glory, Mint Green, Ash Grey, Dusty Grey, Aquamarine, Paw Paw, Whisper, Warm Cream, Raspberry, Sunshine Yellow, Black, Blue Lagoon, Blue Blossom, Harvest Yellow, Mango Squash, Hot Sauce, Violet Harmony, Sunspray, Radiance

COVERAGE RATE

Approximately 400 ft²/gallon (38 m²) at 1.5 mils DFT dependent on surface porosity.

SUGGESTED USES

On properly primed surfaces including wood, vinyl, aluminum, drywall, wood trim, window masonry, galvanized and ferrous metal.



PRODUCT DATA SHEET

EDGE CHEM JAMAICA LIMITED
18 Carifta Avenue
Kingston 11, Jamaica
Tel: (876) 937-3831-4 Fax: 937-3838
E-mail: edge@cwjamaica.com
Website: www.edgechem.com

COLOR GLOW LOW SHEEN EMULSION

Rev. 2 T.D.S.

SURFACE PREPARATION

Surface must be free of dirt, grease, wax, rust, mildew, fungus, chalk and peeling paint. Glossy surface should be sanded. Check adhesion to suspected alkyd or oil paint in an area prior to applying latex coatings. If an adhesion problem is present, prime with a suitable primer to form an intermediate coat. New or unpainted surfaces should be cured properly then coated with one (1) coat of EDGE CHEM CONCRETE SEALER before application.

APPLICATION

Stir Color Glow Low Sheen Emulsion thoroughly before application. If using a brush or roller no reduction is required – use full body. If necessary, thin with water, no more than ½ pint per gallon. If spraying, reduction of up to 1 pint of water per gallon is allowed.

SHELF LIFE

2 years

CLEAN-UP

This should be done immediately using clean water. Wash out brushes, rollers and hands immediately after painting.

