

PRODUCT DATA SHEET

EDGE CHEM JAMAICA LIMITED
18 Carifta Avenue
Kingston 11, Jamaica
Tel: (876) 937-3831-4 Fax: 937-3838
E-mail: edge@cwjamaica.com
Website: www.edgechem.com

CONCRETE PRIMER

Rev. 1 T.D.S.

DESCRIPTION

EdgeChem Concrete Primer is a quality styrene acrylic primer designed for use on new masonry walls, drywall and hardboard. It is formulated to provide excellent adhesion to all masonry surfaces and is compatible with all emulsion topcoats.

PERFORMANCE FEATURES

- Interior & exterior use
- Non-toxic
- Good Alkali resistance
- Low odour
- Easy application
- Water-based
- Flat finish
- Good Adhesion
- Improves bonding of the topcoat
- Enhances performance of the top coat

PHYSICAL PROPERTIES


Specific Gravity (g/cm ³)	: 1.3 ± 0.1
Finish	: Flat
Gloss	: ≤ 5°/85°
Viscosity	: ~ 5500 cPs
Flash Point	: Water-based
Drying Time (31° and 70% RH):-	
To Touch	: approximately 15 minutes (Dependent on temperature and relative humidity)
To Re-coat	: after 1 hour
Colour	: White

COVERAGE RATE

Approximately 380 ft² (35 m²) per gallon depending on surface porosity and texture.

SUGGESTED USES

As a primer on new interior, exterior concrete and cement surfaces.



PRODUCT DATA SHEET

EDGE CHEM JAMAICA LIMITED
18 Carifta Avenue
Kingston 11, Jamaica
Tel: (876) 937-3831-4 Fax: 937-3838
E-mail: edge@cwjamaica.com
Website: www.edgechem.com

CONCRETE PRIMER

Rev. 1

T.D.S.

SURFACE PREPARATION

Fill all cracks and crevices with an appropriate filler. Surface must be free of dirt, grease, wax, mildew, fungus, chalk and peeling paint. New or unpainted surfaces should be properly cured for at least thirty (30) days before priming with EdgeChem Concrete Primer.

If the concrete surface is very smooth apply a concrete etching solution to roughen the surface. Wash surface thoroughly with clean water and allow to dry before priming.

APPLICATION

Stir Concrete Primer thoroughly before application. Apply using a clean brush or roller. No reduction is required, however if necessary, thin with no more than ½ pint of water per gallon of concrete primer.

SHELF LIFE

2 years

CLEAN-UP

This should be done immediately using clean water. Wash out brushes, rollers and hands immediately after painting.

