

## PRODUCT DATA SHEET

EDGE CHEM JAMAICA LIMITED  
18 Carifta Avenue  
Kingston 11, Jamaica  
Tel: (876) 937-3831-4 Fax: 937-3838  
E-mail: [edge@cwjamaica.com](mailto:edge@cwjamaica.com)  
Website: [www.edgechem.com](http://www.edgechem.com)

# EDGE CHEM MATTE VARNISH

Rev. 1 T.D.S.

### DESCRIPTION

EdgeChem Matte Varnish is a high quality polyurethane varnish formulated for high performance characteristics on interior and exterior wood surfaces. EdgeChem Matte Varnish brushes and flows easily to give a smooth matte finish. EdgeChem Matte Varnish will resist the most severe weather conditions with its unique blend of ingredients which guarantee a long-lasting matte finish.

### PERFORMANCE FEATURES

- Exterior durability
- Matte Finish
- Resistant to weathering
- Easy application

### PHYSICAL PROPERTIES

Gloss	:	>5% at 60°
Specific Gravity	:	0.91
Flash Point	:	31.6°C (89°F)
Colour	:	Amber
Drying Time @ 25 °C:-		
To Touch	:	2- 3 hours
To Sanding	:	16 hours
To Re-coat	:	16 hours

### COVERAGE

Approximately 350 sq.ft./gallon (depends on surface texture and porosity).

### SUGGESTED USES


For exterior/interior use on wood surfaces such as decks, railings equipment, doors, porches, window sills and furniture where a matte finish is required.

### SURFACE PREPARATION

For previously painted surfaces in good condition, sand well with 150 grit sandpaper. Remove all traces of dust before applying varnish.

For surfaces in poor condition, remove all old and peeling paint and treat as for bare wood.

For bare wood, sand with 80 grit sandpaper. Wipe free of dust with EdgeChem Oil Paint Reducer.



## PRODUCT DATA SHEET

EDGE CHEM JAMAICA LIMITED  
18 Carifta Avenue  
Kingston 11, Jamaica  
Tel: (876) 937-3831-4 Fax: 937-3838  
E-mail: [edge@cwjamaica.com](mailto:edge@cwjamaica.com)  
Website: [www.edgechem.com](http://www.edgechem.com)

# EDGE CHEM MATTE VARNISH

Rev. 1 T.D.S.

### APPLICATION

Apply a sealer coat of varnish (reduce 10% with Oil Paint Reducer), then apply full body allowing 15-18 hours between coats. Sand with 220 grit sandpaper between coats.

Thin only if necessary with EdgeChem Oil Paint Reducer. Do not exceed 10% by volume.

### SHELF LIFE

2 years

### CLEAN-UP

Clean up with EdgeChem Oil Paint Reducer.

