

PRODUCT DATA SHEET

EDGECHEM JAMAICA LIMITED

18 Carifta Avenue Kingston 11, Jamaica

Tel: (876) 937-3831-4 Fax: 937-3838

E-mail: edge@cwjamaica.com Website: www.edgechem.com

EDGECHEM STAIN VARNISH

Rev. 2 T.D.S.

DESCRIPTION

EdgeChem Stain Varnish is a combination of a polyurethane varnish and a stain. It is designed for use on new and old wooden surfaces and affords its user with economy of time and money with its 'two-in-one' properties. EdgeChem Stain Varnish add rich colour to wooden surfaces and simultaneously preserves the stain with a highly durable finish. It gives a hard wearing, glossy finish.

PERFORMANCE FEATURES

- Interior & exterior durability
- High Gloss
- Resistant to weathering
- Easy application

PHYSICAL PROPERTIES

Gloss : >85% at 60°

Specific Gravity : 0.91

Flash Point : 35°C (95°F)

Colour : Mahogany, Light Oak, Walnut, Dark Oak, Antique Black

Drying Time @ 25 °C:-

To Touch : 2 - 4 hours
To Re-coat : 14-16 hours

COVERAGE

Approximately 9-10 m²/L (375-425 sq.ft./gallon) depending on surface condition and absorbency.

SUGGESTED USES


For exterior/interior use on wooden surfaces such as decks, railings equipment, doors, porches, window sills, cabinets, etc.

SURFACE PREPARATION

New Wooden Surfaces:

Rub down with fine sand paper and dust off all loose materials. Ensure that the surface is dry and clear of all dirt, dust, oil and grease and other debris. Putty all nail holes, cracks and crevices. Then apply a sealer coat of Stain Varnish by brush, roller or spray. Follow with one or two coats of EdgeChem Stain Varnish.

01/2013 56 EDGECHEM JAMAICA LIMITED



PRODUCT DATA SHEET

EDGECHEM JAMAICA LIMITED

18 Carifta Avenue Kingston 11, Jamaica

Tel: (876) 937-3831-4 Fax: 937-3838

E-mail: edge@cwjamaica.com Website: www.edgechem.com

EDGECHEM STAIN VARNISH

Rev. 2 T.D.S.

Previously Varnished Wooden Surfaces:

Remove any loose, flaking, cracking, crazing, peeling semi- adherent varnish, dirt, dust, oil, grease and other debris. Fill all holes, cracks, crevices with putty. Rub down with abrasive paper to obtain a smooth firm surface. Overcoat with one or two coats of EdgeChem Stain Varnish as desired.

APPLICATION

By brush or spray. Supplied ready for use but may be thinned with EdgeChem Oil Paint Reducer if necessary. Do not exceed 5% by volume.

SHELF LIFE

2 years

CLEAN-UP

Clean up with EdgeChem Oil Paint Reducer.



01/2013 57 EDGECHEM JAMAICA LIMITED