

PRODUCT DATA SHEET

EDGE CHEM JAMAICA LIMITED
18 Carifta Avenue
Kingston 11, Jamaica
Tel: (876) 937-3831-4 Fax: 937-3838
E-mail: edge@cwjamaica.com
Website: www.edgechem.com

EDGESPIRIT TINTING SYSTEM

Rev. 0 T.D.S.

DESCRIPTION

EdgeChem Edgespirit is a point of sale tinting system available at select locations. It is formulated from high quality base paints using universal colorants. It offers a selection of over one thousand professionally designed colours to make a professional statement inside and outside your home. Choose from the EdgeSpirit Portfolio Pro fandeck and have your colour mixed in Flat Emulsion, Low Sheen Emulsion or Gloss Oil from the EDGESPIRIT Tinting System.

PERFORMANCE FEATURES

- Interior & exterior durability
- Non-toxic
- Resistant to fungus and mildew
- Low odour
- Easy application
- Excellent color retention

PHYSICAL PROPERTIES

Drying Time:-

(31° and 70% RH)	:	Dependent on temperature and relative humidity:
Colour	:	See EdgeSpirit Portfolio Pro Fandeck
Finish	:	Available in Flat Emulsion, Low Sheen Emulsion, and Gloss Oil

Flat and Low Sheen Emulsion

To Touch	:	approximately 15 minutes
To Re-coat	:	after 1 hour

Gloss Oil

To Touch	:	4 hours
To Re-coat	:	24 hours


COVERAGE RATE

Approximately 400 ft²/gallon (38 m²) at 1.5 mils DFT dependent on surface porosity.

SURFACE PREPARATION

Surface must be free of dirt, grease, wax, rust, mildew, fungus, chalk, peeling paint and all other foreign substances. Glossy surface should be sanded. For Flat and Low sheen Edgespirit colours check adhesion to suspected alkyd or oil paint in an area prior to applying latex coatings. If an adhesion problem is present, prime with a suitable primer to form an intermediate coat.

New or unpainted surfaces should be cured properly then coated with an appropriate primer before application of Edgespirit topcoat.



PRODUCT DATA SHEET

EDGE CHEM JAMAICA LIMITED
18 Carifta Avenue
Kingston 11, Jamaica
Tel: (876) 937-3831-4 Fax: 937-3838
E-mail: edge@cwjamaica.com
Website: www.edgechem.com

EDGESPIRIT TINTING SYSTEM

Rev. 0

T.D.S.

APPLICATION

Stir thoroughly before application. If using a brush or roller no reduction is required – use full body. If necessary, thin Edgespirit Flat and Low Sheen Emulsion with water, no more than ½ pint per gallon. If spraying, reduction of up to 1 pint of water per gallon is allowed.

If spraying EdgeSpirit Gloss Oil reduce by 10% using Edgechem Oil Paint Reducer (**1 pint reducer to 1 gallon paint**). Paint spatters or drops must be cleaned immediately with the reducer.

SHELF LIFE

Edgespirit Flat and Low Sheen	-	1 year
Edgespirit Gloss Oil	-	2 Years

CLEAN-UP

This should be done immediately after painting.

For Edgespirit Flat and Low Sheen Emulsion wash out brushes and rollers with clean water.

For Edgespirit Gloss Oil clean brushes, roller and spray equipment using EdgeChem Oil Paint Reducer.

