



PRODUCT DATA SHEET

EDGE CHEM JAMAICA LIMITED
18 Carifta Avenue
Kingston 11, Jamaica
Tel: (876) 937-3831-4 Fax: 937-3838
E-mail: edge@cwjamaica.com
Website: www.edgechem.com

FURNITURE PUTTY

Rev. 2

T.D.S.

DESCRIPTION

EdgeChem Furniture Putty is a Polyester based body putty which is catalyzed with Benzoyl Peroxide (B.P.O. Cream Hardener).

PERFORMANCE FEATURES

- Very fast cure
- Easy sand ability
- Excellent adhesion and filling properties for wooden surfaces.
- Exceptional storage stability.

PHYSICAL PROPERTIES

Specific Gravity	:	1.44g
Flash Point	:	22.7 °C (73 °F)
Colour	:	Wood coloured
Drying Time:-		
To Touch	:	5 minutes
To Sand	:	15 minutes

COVERAGE RATE

Approximately 32 square feet per gallon.

SUGGESTED USES

For the repair of damaged wooden furniture and for concealing imperfections in wood.

SURFACE PREPARATION

All loose particles, dust and shavings must be removed from surface.

APPLICATION

Use furniture putty – to the size of an egg – add one (1) inch of B.P.O. Hardener. Knead hardener and putty thoroughly to a uniform colour. Use mixture to fill damaged area. Build up putty slightly higher than surrounding area as this allows for feather-edging. After approximately fifteen (15) minutes the product may be sanded to desired smoothness.

SHELF LIFE

1 year

CLEAN-UP

Clean up using EdgeChem Lacquer Thinner.