



## PRODUCT DATA SHEET

EDGE CHEM JAMAICA LIMITED  
18 Carifta Avenue  
Kingston 11, Jamaica  
Tel: (876) 937-3831-4 Fax: 937-3838  
E-mail: [edge@cwjamaica.com](mailto:edge@cwjamaica.com)  
Website: [www.edgechem.com](http://www.edgechem.com)

# NITROCELLULOSE HIGH GLOSS LACQUER

Rev. 3 T.D.S.

### DESCRIPTION

EdgeChem High Gloss Lacquer is a nitrocellulose based lacquer designed for interior use on wooden furniture where a full gloss appearance is required.

### PERFORMANCE FEATURES

- Extremely fast air dry
- Sands freely
- High build
- No lifting under lacquers
- No critical re-coat time

### PHYSICAL PROPERTIES

Gloss	:	>88% at 60°
Specific Gravity	:	0.93
Viscosity	:	320-340 cPs (#4 Ford Cup at 25°C)
Flash Point	:	5°C (40°F)
Colour	:	Amber
Drying Time:-		
To Touch	:	5-10 minutes
To Handle	:	30 minutes
To Re-coat	:	15-30 minutes

### SUGGESTED USES

For use on interior wooden surfaces and furniture.

### SURFACE PREPARATION

Surface must be dry and free of grease, oil and dirt. Moisture content of wood should be below 8%. Use over wood products that have previously been sealed with Sanding Sealer and sanded to a very smooth finish (400-600 grit sand paper). Badly damaged or poor surface must be stripped to bare wood and treated as new.

### APPLICATION

Reduce two (2) parts Lacquer to one (1) part Lacquer Thinner. Apply 2-3 coats of mixture at 40-50 psi. Recoat at intervals of ten (10) minutes to an hour depending on climatic conditions. To prevent blushing associated with high humidity use EdgeChem Retarder Solvent as directed.

### SHELF LIFE

1 year

### CLEAN-UP

Clean up with EdgeChem Lacquer Thinner.