

PRODUCT DATA SHEET

EDGE CHEM JAMAICA LIMITED
18 Carifta Avenue
Kingston 11, Jamaica
Tel: (876) 937-3831-4 Fax: 937-3838
E-mail: edge@cwjamaica.com
Website: www.edgechem.com

ROAD MARKING PAINT

Rev. 2 T.D.S.

DESCRIPTION

EdgeChem Road Marking Paint is an alkyd based, quick drying coating which is durable with excellent adhesion and re-coating capabilities.

PERFORMANCE FEATURES

- Quick Drying
- Interior and Exterior use
- Good durability
- Excellent Hiding Power
- Apply with brush, roller or spray

PHYSICAL PROPERTIES

Density (lb/gal)	:	10.6 ± 0.1
Finish	:	Egg Shell
Viscosity (cP)	:	620 - 1000
Flash Point	:	9 °C
Colours	:	White, Yellow, Blue

Drying Time (31° and 70% RH):-

To Touch	:	10 minutes (Dependent on temperature and relative humidity)
To Re-coat	:	after 1 hour

COVERAGE RATE


Varies considerably with method of application and type of surface. One gallon will do a four inch line (120 – 150 meters long).

SUGGESTED USES

EdgeChem Road Marking Paint is suitable for use on new and previously painted bitumen and concrete roads, runways, parking lot surfaces and traffic lanes in industrial plants.

SURFACE PREPARATION

The surface to be coated must be clean, free from dirt, sand, gravel, oil and grease.



PRODUCT DATA SHEET

EDGE CHEM JAMAICA LIMITED
18 Carifta Avenue
Kingston 11, Jamaica
Tel: (876) 937-3831-4 Fax: 937-3838
E-mail: edge@cwjamaica.com
Website: www.edgechem.com

ROAD MARKING PAINT

Rev. 2

T.D.S.

APPLICATION

Stir contents thoroughly before using. If using a brush or roller apply without thinning. If spraying, reduce by 5-10%, with EdgeChem Industrial Thinner. The paint will touch dry in ten (10) minutes and hard dry in one (1) hour.

DO NOT apply Road Marking Paint during rainy weather, as this could affect the initial drying and curing of the product.

SHELF LIFE

2 years

CLEAN-UP

This should be done immediately using EdgeChem Industrial Thinner.

