



PRODUCT DATA SHEET

EDGE CHEM JAMAICA LIMITED
18 Carifta Avenue
Kingston 11, Jamaica
Tel: (876) 937-3831-4 Fax: 937-3838
E-mail: edge@cwjamaica.com
Website: www.edgechem.com

SUPER GLOSS SPAR VARNISH

Rev. 2

T.D.S.

DESCRIPTION

EdgeChem Super Gloss Spar Varnish is a high gloss varnish designed for exterior and interior use on wooden surfaces and metal.

PERFORMANCE FEATURES

- High gloss
- High build

PHYSICAL PROPERTIES

Gloss	:	>85% at 60°
Specific Gravity	:	0.91
Flash Point	:	31.6°C (89°F)
Colour	:	Clear lavender
Drying time:-		
To Touch	:	1½ - 2 hours
To Re-coat	:	6-8 hours
Hard dry	:	Overnight

SUGGESTED USES

For use on interior and exterior wooded surfaces.

SURFACE PREPARATION

Sand surface properly and remove dust by blowing with air. Surface should be cleaned with EdgeChem Oil Paint Reducer.

APPLICATION

The first coat of Varnish should be thinned 5% with Oil Paint Thinner when applying to bare wood, use full bodied over Sanding Sealer or aged coatings. Second coating should be applied full bodied.

SHELF LIFE

2 years

CLEAN-UP

Clean up with EdgeChem Oil Paint Thinner.