

PRODUCT DATA SHEET

EDGE CHEM JAMAICA LIMITED
18 Carifta Avenue
Kingston 11, Jamaica
Tel: (876) 937-3831-4 Fax: 937-3838
E-mail: edge@cwjamaica.com
Website: www.edgechem.com

UNIVERSAL PRIMER

Rev. 2

T.D.S.

DESCRIPTION

EdgeChem Universal Primer is a fast drying, rust inhibitive, modified alkyd metal primer, offering excellent corrosion resistance for Iron and Steel. The product is chromate free and may be top-coated with a wide range of industrial topcoats.

PERFORMANCE FEATURES

- Fast drying
- Good metal protection
- Exceptional storage stability

PHYSICAL PROPERTIES

Specific Gravity	:	1.30
Flash Point	:	40°C (112°F) based on major solvent component
Shelf Life	:	2 years
Gloss	:	Slight
Colour	:	Yellow
Drying Time:-		
To Touch	:	30 minutes
Hard dry	:	24 hours
Re-coat time	:	overnight

COVERAGE RATE

Approximately 380 – 400 square feet per gallon.


SUGGESTED USES

For interior and exterior use over ferrous and non-ferrous metals. These include structural steel, equipment, tanks, implements, catwalks, stairs, railing, conveyers, and for general maintenance painting.

SURFACE PREPARATION

The surface to be painted must be clean and dry, free of dust, dirt, oil, grease and any other contaminant to ensure optimum adhesion and coatings performance properties.

Iron and steel surfaces must be clean, free of oil, grease, loose paint, rust and mill scale. Commercial blast cleaning is highly recommended. The minimum surface preparation recommendation is hand tool clean.



PRODUCT DATA SHEET

EDGE CHEM JAMAICA LIMITED
18 Carifta Avenue
Kingston 11, Jamaica
Tel: (876) 937-3831-4 Fax: 937-3838
E-mail: edge@cwjamaica.com
Website: www.edgechem.com

UNIVERSAL PRIMER

Rev. 2

T.D.S.

APPLICATION

This coating may be applied by brush, roller, conventional spray or airless spray. Care must be taken to achieve the specific wet and dry film thicknesses. Even coats, free from sags, drips, streaks and bubbles must be obtained.

No reduction necessary for brush and roller application. Reduce as needed up to 10% by volume with EdgeChem Industrial Thinner for spray application.

SHELF LIFE

2 years

CLEAN-UP

Clean up with EdgeChem Industrial Thinner.

