



EDGECEM JAMAICA LIMITED
18 Carifta Avenue
Kingston 11, Jamaica
Tel: (876) 937-3831-4 Fax: 937-3838
E-mail: edge@cwjamaica.com
Website: www.edgechem.com

PRODUCT DATA SHEET

Rev. 0

T.D.S.

Urethane Super Fast Hardener

DESCRIPTION

EdgeChem's Urethane Fast Hardener is a medium-solids isocyanate hardeners for use with EdgeChem's Automel Super Clear, Automel Enamel and Industrial Quick Dri topcoat systems, as well as EdgeChem's Autoprime Filler.

PHYSICAL CHARACTERISTICE

Viscosity @ 27°C	:	25 – 35 sec
Specific Gravity	:	0.96 – 0.99

SUGGESTED USES

- Urethane Fast Hardener is suitable for spot and panel repair
- Urethane Fast Hardener is suitable for use with Automel Super Clear, Autoprime Filler

SURFACE PREPARATION

See Data Sheet and labels for the Edgechem products in which the Urethane Fast Hardener is recommended for use.

04/2016

EDGECEM JAMAICA LIMITED

The suggestions recommendations and technical data in this document are based on information we believe to be valid. However, they are offered without guarantee as application and methods of use of our products are beyond our control. We recommend that users evaluate our materials before adopting them for commercial uses. Suggestions for use of our products should not be understood as recommendations that may be used in violation of any patent.

Urethane Super Fast Hardener

APPLICATION

See technical data sheets for the Edgechem product listed below:

Automel Super Clear
Automel Enamel
Industrial Quick Dri Enamel
Autoprime Filler

SHELFLIFE

1 Year

CLEAN UP

See data sheet for Edgechem products use in.